

# Test

August 2, 2004

## 1 Normal

Table "public.suites"

<i>Column</i>	<i>Type</i>	<i>Modifiers</i>
id	integer	not null default nextval('public.suites_id_seq'::text)
name	text	not null
archive_id	integer	not null
version	text	
path	text	
alias	text	
description	text	

Indexes:

"suites\_pkey" PRIMARY KEY, btree (id)

"suites\_alias\_key" UNIQUE, btree (alias)

"suites\_name\_key" UNIQUE, btree (name)

Foreign-key constraints:

"suites\_archive\_ref" FOREIGN KEY (archive\_id) REFERENCES archives(id)

Table "public.suites"

<i>Column</i>	<i>Type</i>	<i>Modifiers</i>
id	integer	not null default nextval('public.suites_id_seq'::text)
name	text	not null
archive_id	integer	not null
version	text	
path	text	
alias	text	
description	text	

Indexes:

"suites\_pkey" PRIMARY KEY, btree (id)

"suites\_alias\_key" UNIQUE, btree (alias)

"suites\_name\_key" UNIQUE, btree (name)

Foreign-key constraints:

"suites\_archive\_ref" FOREIGN KEY (archive\_id) REFERENCES archives(id)

Table "public.suites"

<i>Column</i>	<i>Type</i>	<i>Modifiers</i>
id	integer	not null default nextval('public.suites_id_seq'::text)
name	text	not null
archive_id	integer	not null
version	text	
path	text	
alias	text	
description	text	

Indexes:

"suites\_pkey" PRIMARY KEY, btree (id)

"suites\_alias\_key" UNIQUE, btree (alias)

"suites\_name\_key" UNIQUE, btree (name)

Foreign-key constraints:

"suites\_archive\_ref" FOREIGN KEY (archive\_id) REFERENCES archives(id)

Table "public.suites"

*Record 1*

Column id  
Type integer  
Modifiers not null default nextval('public.suites\_id\_seq'::text)

*Record 2*

Column name  
Type text  
Modifiers not null

*Record 3*

Column archive\_id  
Type integer  
Modifiers not null

*Record 4*

Column version  
Type text  
Modifiers

*Record 5*

Column path  
Type text  
Modifiers

*Record 6*

Column alias  
Type text  
Modifiers

*Record 7*

Column description  
Type text  
Modifiers

Indexes:

"suites\_pkey" PRIMARY KEY, btree (id)

"suites\_alias\_key" UNIQUE, btree (alias)

"suites\_name\_key" UNIQUE, btree (name)

Foreign-key constraints:

"suites\_archive\_ref" FOREIGN KEY (archive\_id) REFERENCES archives(id)

Table "public.suites"

<i>Record 1</i>	
Column	id
Type	integer
Modifiers	not null default nextval('public.suites_id_seq'::text)
<i>Record 2</i>	
Column	name
Type	text
Modifiers	not null
<i>Record 3</i>	
Column	archive_id
Type	integer
Modifiers	not null
<i>Record 4</i>	
Column	version
Type	text
Modifiers	
<i>Record 5</i>	
Column	path
Type	text
Modifiers	
<i>Record 6</i>	
Column	alias
Type	text
Modifiers	
<i>Record 7</i>	
Column	description
Type	text
Modifiers	

Indexes:

"suites\_pkey" PRIMARY KEY, btree (id)

"suites\_alias\_key" UNIQUE, btree (alias)

"suites\_name\_key" UNIQUE, btree (name)

Foreign-key constraints:

"suites\_archive\_ref" FOREIGN KEY (archive\_id) REFERENCES archives(id)

Table "public.suites"

<i>Record 1</i>	
Column	id
Type	integer
Modifiers	not null default nextval('public.suites_id_seq'::text)
<i>Record 2</i>	
Column	name
Type	text
Modifiers	not null
<i>Record 3</i>	
Column	archive_id
Type	integer
Modifiers	not null
<i>Record 4</i>	
Column	version
Type	text
Modifiers	
<i>Record 5</i>	
Column	path
Type	text
Modifiers	
<i>Record 6</i>	
Column	alias
Type	text
Modifiers	
<i>Record 7</i>	
Column	description
Type	text
Modifiers	

Indexes:

"suites\_pkey" PRIMARY KEY, btree (id)

"suites\_alias\_key" UNIQUE, btree (alias)

"suites\_name\_key" UNIQUE, btree (name)

Foreign-key constraints:

"suites\_archive\_ref" FOREIGN KEY (archive\_id) REFERENCES archives(id)